

Pneumatic Plier

95/16-418

The BeA Pneumatic Plier 95/16-418 clinches various materials securely with staples from 1/4" to 5/8" in length. The pressure of the clinching jaw is controlled so that the work material is gently pressed against prior to the staple being driven. The throat depth of 5.9" allows fastening even in hard to reach areas. This tool is also available a long-magazine.

Popular Applications

Clinching of: Paper, cardboard, foil, fabric, leather, bag headers, etc.



Technical Data

Model:	95/16-418 Standard	95/16-418 L Long-magazine
Part number:	12000060	12000061
Loading type:	bottom loading	bottom loading
Fastener type:	95	95
Magazine capacity:	114	214
Standard load, strips x fasteners/strip:	1 x 100	2 x 100
Working pressure:	75-90 P.S.I.	75-90 P.S.I.
Maximum air pressure:	90 P.S.I.	90 P.S.I.
Air consumption:	.024 cu. ft./cycle @ 90 P.S.I.	.024 cu. ft./cycle @ 90 P.S.I.
Recommended hose I.D.:	ø 3/8"	ø 3/8"
Weight:	3.08 lbs.	3.61 lbs.

Items supplied with tool: Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

Accessories

Part number	Description
14403330	Remote firing valve

All BeA pneumatic tools can be jig mounted.
We supply the necessary accessories.



This tool conforms to the EC Directive
for Machinery (89/392 EWG)


Pneumatic Plier

95/16-418



BeA Fasteners U.S.A.
2100-120 Fairfax Road
Greensboro, NC 27407
Phone: (336) 510-4232
Fax: (336) 510-4233

Fastener type 95



Description	L = Length in.
95/06 NK	1/4"
95/08 NK	5/16"
95/10 NK	3/8"
95/12 NK	1/2"
95/14 NK	9/16"
95/16 NK	5/8"

Other lengths and finishes are also available on request.

Fastener nomenclature:

NK = Galvanized steel
NKS = Galvanized steel, high carbon
BK = Brite steel
BKS = Brite steel, high carbon

HZ = Resin coated
NR = Stainless steel
DP = Divergent point