

# Pneumatic Plier

## 380/16-419

The BeA Pneumatic Plier 380/16-419 guarantees secure of a variety of materials. The pressure of the clinching jaw is controlled so that the work material is gently pressed against prior to the staple being driven. The deep jaw throat allows fastening even in hard to reach areas.

### Popular Applications

Clinching of: Paper, cardboard, foil, fabric, leather, bag headers, etc.



### Technical Data

Model:	<b>380/16-429</b> Standard
Part number:	12000062
Loading type:	bottom loading
Fastener type:	380
Magazine capacity:	160
Standard load, strips x fasteners/strip:	1 x 150
Working pressure:	75-90 P.S.I.
Maximum air pressure:	90 P.S.I.
Air consumption:	.24 cu. ft./cycle @ 90 P.S.I.
Recommended hose I.D.:	ø 3/8"
Weight:	3.08 lbs.

Items supplied with tool: Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

### Accessories

Part number	Description
14406013	Card board support
14403330	Remote firing valve

All BeA pneumatic tools can be jig mounted.  
We supply the necessary accessories.



This tool conforms to the EC Directive  
for Machinery (89/392 EWG)


# Pneumatic Plier

## 380/16-419



BeA Fasteners U.S.A.  
2100-120 Fairfax Road  
Greensboro, NC 27407  
Phone: (336) 510-4232  
Fax: (336) 510-4233

### Fastener type 380



Description	L = Length inches
380/06 NK	1/4"
380/08 NK	5/16"
380/10 NK	3/8"
380/12 NK	1/2"
380/14 NK	9/16"
380/16 NKS	5/8"

Other lengths and finishes are also available on request.

### Fastener nomenclature:

NK = Galvanized steel  
NKS = Galvanized steel, high carbon  
BK = Brite steel  
BKS = Brite steel, high carbon

HZ = Resin coated  
NR = Stainless steel  
DP = Divergent point