

Pneumatic Tacker Type 92/32 – 612 L

A lightweight and particularly well balanced tool
The compact design of the 92/32-612 tacker makes an ideal tool for high speed applications and for getting into hard to reach staple placements. This efficient tacker drives staples type 92 in length from 15 to 32 mm. The long magazine reduces time spent loading. The cycle speed of the automatic version can be infinitely varied between 0 – 600 staples per minute.



Popular applications:

Case goods, door and window manufacturing, building siding, case backs, trim work.

Length: 340mm
Width: 56,5 mm
Height: 198 mm

Technical data

Type description:	92/32-612 L	92/32-612 AL
	Long magazine / Single	Automatic - Long magazine
Article code:	12000211 / 12000213	12000214
Magazine type :	Top loader	Top loader
Safety:	Contact actuation / Single actuation	Contact actuation
Fastener type:	Type 92	Type 92
Magazine capacity:	215	215
Fasteners per strip:	2 x 100	2 x 100
Operating pressure:	5 – 8 bar	5 – 8 bar
Max. operating pressure:	8 bar	8 bar
Air consumption/operation:	0,9 litre / 6 bar	0,9 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 79 dB	L pA, 1s, d= 79 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 87 dB	L WA, 1 s,d= 87 dB
Weight:	1,33 kg	1,7 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer.
For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

Articel code	Description
14400847	Roller Edge Guide, resilient and for L + AL
14400902	Guide plate with high-adjustable stop for L
14403421	Remote Valve
14403527	Mounting flange

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive
for Machinery (89/392 EWG)

Pneumatic Tacker Type 92/32-612 L

Staples type 92



BeA Deutschland
Befestigungstechnik GmbH
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com



Description	L = Length mm
92/15 NK HZ	15
92/18 NK HZ	18
92/21 NK HZ	21
92/25 NK HZ	25
92/28 NK HZ	28
92/30 NK HZ	30
92/32 NK HZ	32

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut