

FasTagger II

The FastTagger II is designed to staple poly bar code labels onto the ends of lumber. The FastTagger II automatically staples labels to the ends of lumber, cuts the label off its roll, and feeds the next tag into position to be stapled. Four different sizes of labels can be used in the FastTagger II. Adjusting the tool for different label sizes can be done in less than 10 seconds. The FastTagger II weighs just 6.5 lbs. including a full roll of tags.



Applications

Bar code labeling of lumber

Technical Data


Model:	FasTagger II
Product code number:	12000518
Staple magazine type:	Bottom load
Staple type:	71 (Leg length 10mm)
Label sizes:	11/16" x 1 3/8"
	11/16" x 2 3/4"
	7/8" x 1 3/8"
	7/8" x 2 3/4"
Magazine capacity:	190 staples
Standard load:	1 strips @ 182 staples
Operating pressure:	75 - 90 P.S.I.
Air consumption:	.05 cu. ft./second @ 90 P.S.I.
Recommended hose I.D.:	3/8"
Dimensions L/W/H:	10 3/4" x 5 1/4" x 10 7/8"
Weight:	5.5 lbs. (6.5 lbs. loaded w/full roll of labels)

Accessories

Part number	Description
14403330	Remote actuating valve

FasTagger II Bar Code Labeling Stapler

Stapler type 71



Part Number	Description	Length Inches
10000112	71/10 NK	3/8"
10000125	71/12 NK	1/2"
10001777	71/14 NK	9/16"

Labels should be ordered directly from Weber Marketing Systems (847) 364-8500

Fastener nomenclature:

NK = Galvanized steel	HZ = Resin coated
NKS = Galvanized steel, high carbon	NR = Stainless steel
BK = Brite steel	DP = Divergent point
BKS = Brite steel, high carbon	