



Easy to  
Adjust

# BeA SelectFlare

## 92/25-553 FCS

Work Contact

- BeA flaring tool for mattress, bedding and fabric to foam applications
- Work contact allows bump-fire operation for precise and quick stapling
- Screwless adjustment, speeds up operation
- Simple dial to adjust flaring of staples, consistent results with each shot
- Dial indicator
- Bottom load for quick reloading
- Low recoil, cushioned grip for improved operator safety
- Improve efficiency, decrease service intervals
- Quick and accurate application of 92 series staples
- Accepts BeA 92 series staples up to 1" (25mm)
- Quality made in Germany and the USA



### Applications

Bedding, Mattresses, Fabric to foam



## BeA 92/25-553 FCS

### Technical Data




Type description	92/25-553FCS
Item code	12100515
Magazine type	bottom loading
Fastener type	BeA 92 up to 1" (25mm)
Magazine capacity	120
Fasteners per strip	100
Operating pressure	75 - 90 PSI
Max operating pressure	90 PSI
Air consumption/operation	.016 cu. ft./cycle @ 90 PSI
Inner hose diameter	3/8"
Emission sound pressure level at the workstation	L pA, 1s = 85 dB
Single-shot emission sound pressure level	L pA, 1s = 93 dB
Weight	3.1 lbs (1.4 kg)
Vibration level	less than 2.5m/sec2
Accessories supplied with tool	Operating instructions, spare parts list service instructions

Subject to technical modifications


### 92/25-553 FCS Dial Adjustment

Turn dial to achieve desired flaring of staples


1



2



3



BeA Fasteners USA, Inc.  
(336) - 510 - 4232  
(336) - 510 - 4233 (fax)  
[www.bea-group.com](http://www.bea-group.com)  
[info@us.bea-group.com](mailto:info@us.bea-group.com)