

# Pneumatic Tacker

## 380/16-429 LN

A variation of the successful upholstery tacker 380/16-420. The long 2" nose addresses a variety of applications, especially in hard to reach areas. The benefits of the BeA Pneumatic Tacker 380/16-429 LN are its light weight, excellent driving power, combined with integrated silencer, and low air consumption.

### Popular Applications:

Upholstery, weather stripping, cabinetry, insulation, picture frames, boat seating, wicker work.



### Technical Data

Model:	<b>380/16-429 LN</b>
	Standard
Part number:	12000073
Loading type:	bottom loading
Fastener type:	80/380
Magazine capacity:	157
Standard load, strips x fasteners/strip:	1 x 150 Type 380 1 x 125 Type 80
Working pressure:	75-90 P.S.I.
Maximum air pressure:	90 P.S.I.
Air consumption:	.0176 cu. ft./cycle @ 90 P.S.I.
Recommended hose I.D.:	ø 3/8"
Weight:	2.27 lbs.

Items supplied with tool: Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

### Accessories

Part number	Description
14403330	Remote firing valve assembly
14406168	Special back nose assembly for 6mm and shorter staples only

All BeA pneumatic tools can be jig mounted.  
We supply the necessary accessories.



This tool conforms to the EC Directive  
for Machinery (89/392 EWG)


# Pneumatic Tacker

## 380/16-429 LN



BeA Fasteners U.S.A.  
2100-120 Fairfax Road  
Greensboro, NC 27407  
Phone: (336) 510-4232  
Fax: (336) 510-4233

### Fastener type 80 / Type 380



Description	L = Length in
80/03 NK	1/8"
80/04 NK	5/32"
80/05 NK	3/16"
380/06 NK	1/4"
380/08 NK	5/16"
380/10 NK	3/8"
380/12 NK	1/2"
380/14 NK	9/16"
380/16 NKS	5/8"

Other lengths and finishes are also available on request.

#### Fastener nomenclature:

NK = Galvanized steel  
NKS = Galvanized steel, high carbon  
BK = Brite steel  
BKS = Brite steel, high carbon

HZ = Resin coated  
NR = Stainless steel  
DP = Divergent point