

## T-Nailer Type T 25-155

A lightweight tool with compact design for driving T-nails, in shank lengths from 13 to 25 mm. The ideal tool for fastening metal sheets and aluminum mouldings as well as applications in truck and trailer construction.

The BeA nailer T 25-155 RapidClip is equipped with a special attachment to fasten RapidClip at tubular-steel.



### Popular applications:

Fastening of metal sheets, aluminium mouldings, truck and trailer construction. RapidClip at tubular-steel.

Length: 295 mm  
Width: 70 mm  
Height: 248 mm

### Technical data

Type description:	<b>T 25-155 Standard</b>	<b>T25 – 155 Rapidclip</b>
Article code:	12200017	12000244
Magazine type :	Top loader	Oberlader
Safety	Contact actuation	Single actuation
Fastener type:	Type T	T
Magazine capacity:	82	82
Nails per coil:	2 x 33	2 x 33
Operating pressure:	6 – 8 bar	6 – 8 bar
Max. operating pressure:	8 bar	8 bar
Air consumption/operation:	1.5 litre / 6 bar	1.5 Liter 6 bar
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW
Emission sound pressure level at the workstation:	L pA, 1s, d= 79 dB	L pA, 1s, d= 79 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 87 dB	L WA, 1 s,d= 87 dB
Weight:	2.7 kg	2.7 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is 4 m/s²

**Extras supplied with the nailer:** Operating instructions, spare parts list, service instructions  
For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

### Accessories:

Article code	Description
14403409	Remote valve with safety yoke
14403402	Remote valve
14403442	Mounting flange, complete
14400891	High adjustable stop
14406201	Single actuation set
14406959	Grip elongation

All BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive  
for Machinery (89/392 EWG)

Product leaflet 155 to 25 mm


## T-Nailer Type T 25-155

### Nails Type T



BeA Deutschland  
Befestigungstechnik  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: (04102) 78-0  
Fax: (04102) 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)

a division of  
Joh. Friedrich Behrens AG



Description	L = Length mm
T 13 NKS	13
T 15 NKS	15
T 18 NKS	18
T 21 NKS	21
T 25 NKS	25



Other lengths and finishes are also available on request.

#### Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut